

RESTROOM FACILITY

SAU TECH
CAMDEN, ARKANSAS

PROJECT INFORMATION

DRAWINGS AND PROJECT MANUAL APPROVED AND IDENTIFIED AS PARTS OF THE OFFICIAL CONTRACT DOCUMENT

OWNER: SAU TECH
FACILITY: RESTROOM FACILITY
LOCATION: CAMDEN, ARKANSAS
BY: _____
DATE: _____

ARCHITECT: LEWIS, ELLIOTT, MCMORRAN, VADEN,
RAGSDALE, & WOODWARD INCORPORATED
ADDRESS: 11225 HURON LANE, SUITE 104
LITTLE ROCK, ARKANSAS 72211
BY: _____
DATE: _____

PROJECT NUMBER: 24093
DRAWINGS AND PROJECT MANUAL DATED: 2025 03-17


MATERIAL LEGEND

CMU (PLAN)
MASONRY (PLAN)
METAL STUD FRAMING (PLAN)
GYPSUM PANELS
WOOD BLOCKING CONTINUOUS (SECTION)
WOOD BLOCKING AS NEEDED (SECTION)
WOOD FINISHED FACE OR SOLID WOOD
WOOD PLYWOOD (SECTION)
CONCRETE (SECTION)
RIGID INSULATION (SECTION)
BATT INSULATION (SECTION)
FILL MATERIAL (SECTION)
REPLACED SOIL (SECTION)

DESIGN DATA

GENERAL CODES:
INTERNATIONAL BUILDING CODE (IBC) 2021 EDITION
ARKANSAS FIRE PREVENTION CODE (AFPC) 2021 EDITION
SEISMIC:
SEISMIC RISK CATEGORY II 2021 IBC
SEISMIC DESIGN CATEGORY B
CALHOUN COUNTY AFPC REVISIONS
ACCESSIBILITY STANDARDS
ADA STANDARDS FOR ACCESSIBLE DESIGN 2017 EDITION
TOTAL BUILDING SQUARE FOOTAGE:
175 SQ. FT.

VICINITY MAP



INDEX OF DRAWINGS

T1.1 TITLE SHEET

ARCHITECTURAL

A0.1 FLOOR PLAN AND DETAILS
A1.1 SECTIONS AND ELEVATIONS

STRUCTURAL

S1.1 NOTES
S2.1 PLANS AND DETAILS

PLUMBING

P1.1 FLOOR PLAN - TOILETS - PLUMBING

MECHANICAL

M1.1 FLOOR PLAN - TOILETS - HVAC

ELECTRICAL

E1.1 FLOOR PLAN - ELECTRICAL
E2.1 ELECTRICAL LEGENDS, DETAILS & NOTES

CERTIFICATION STATEMENT:

I HEREBY CERTIFY THAT THESE PLANS AND SPECIFICATIONS HAVE BEEN PREPARED BY ME, OR UNDER MY SUPERVISION. I FURTHER CERTIFY THAT TO THE BEST OF MY KNOWLEDGE THESE PLANS AND SPECIFICATIONS ARE AS REQUIRED BY LAW AND IN COMPLIANCE WITH THE "ARKANSAS FIRE PREVENTION CODE" FOR THE STATE OF ARKANSAS.

LEWIS, ELLIOTT, MCMORRAN, VADEN, RAGSDALE, & WOODWARD, INCORPORATED

[Signature] 3/14/25

SYMBOL LEGEND

100.1 DOOR MARK, SEE DOOR SCHEDULE
A CASEWORK ELEVATION MARK
B WINDOW / STOREFRONT FRAME MARK
CLASSROOM ROOM NAME
101 ROOM NUMBER
LAY-1 9'-4" ROOM CEILING HEIGHT
CEILING FINISH
3 DETAIL / SECTION NUMBER
A4.4 SHEET NUMBER


ABBREVIATIONS

AFF ABOVE FINISH FLOOR
AT ALUMINUM THRESHOLD
CEJC CEILING EXPANSION JOINT COVER
CJ CONTROL JOINT
CLG CEILING
CONC CONCRETE
CONT CONTINUOUS
DTL DETAIL
FD FLOOR DRAIN
FEC FIRE EXTINGUISHER CABINET
FEJ FLOOR EXPANSION JOINT
FLR FLOOR
GB GRAB BAR
MECH MECHANICAL
NHO NORMALLY HELD OPEN
NTS NOT TO SCALE
OPG OPENING
REQ REQUIRED
SHT SHEET
SIM SIMILAR
STO STORAGE
TYP TYPICAL
WEJC WALL EXPANSION JOINT COVER

QTY		DESCRIPTION	CATALOG NUMBER	FINISH	MFR
3	EA	HINGE	5BB1 4.5 X 4.5 NRP	630	IVE
1	EA	CORRIDOR LOCK W/ OUTSIDE INDICATOR	45H 0 TD 15H 630 VIT	360	BES
1	EA	PERMANENT CORE	MATCH EXISTING KEY SYSTEM	626	BES
1	EA	SURFACE CLOSER	4040XP	689	LVE
1	EA	KICK PLATE	8400 10" X 2" LDW B-CS	630	INC
1	EA	GASKETING	188S	BK	ZER
1	EA	DOOR SWEEP	39A	A	ZER
1	EA	THRESHOLD	655A	BK	ZER

MARK	DESCRIPTION	MOUNTING HEIGHT
GB-36	GRAB BAR - 36"	34" A.F.F. to CENTERLINE
GB-42	GRAB BAR - 42"	34" A.F.F. to CENTERLINE
GB-18	VERTICAL GRAB BAR - 18"	40" A.F.F. to BASE
LAV	LAVATORY - WALL MOUNTED	34" A.F.F. to RIM
CH	COAT HOOK	54" A.F.F.
M	MIRROR	24"x36" / 40" A.F.F. to BOTTOM OF REFLECTIVE SURFACE
HCWC	H.C. WATER CLOSET	17" A.F.F. to SEAT


- 4 HOLLOW METAL FRAME
A0.1 3" = 1'-0"




3 HOLLOW METAL FRAME
A0.1 3" = 1'-0"

ROOM IDENTIFICATION		FLOOR	BASE	WALL	CEILING
NAME	#				
RESTROOM	101	SEALED CONCRETE	RUBBER BASE	EPOXY PAINT	PAINT EXPOSED
RESTROOM	102	SEALED CONCRETE	RUBBER BASE	EPOXY PAINT	PAINT EXPOSED

MARK	HW SET	PANEL						FRAME			
		TYPE	WIDTH	HEIGHT	THICK.	MATERIAL	FINISH	MATERIAL	FINISH	DEPTH	HEAD
101.1	145	F	3'-0"	7'-0"	1 3/4"	INSUL. METAL	PAINT	HMF	PAINT	5 3/4"	4"
102.1	145	F	3'-0"	7'-0"	1 3/4"	INSUL. METAL	PAINT	HMF	PAINT	5 3/4"	4"




1 GRAB BAR ELEVATIONS




2 EXTERIOR ALUMINUM THRESHOLD (AT)
A0.1 3" = 1'-0"

1. PROVIDE HOUSEKEEPING AIDS FOR ELECTRICAL AND MECHANICAL EQUIPMENT. VERIFY SIZE AND LOCATION WITH ELECTRICAL, PLUMBING, AND HVAC INSTALLERS AND MANUFACTURERS.
2. FIELD VERIFY ALL DIMENSIONS FOR HANDRAILS, EQUIPMENT, ETC. PRIOR TO FABRICATION AND INSTALLATION
3. PROVIDE WOOD FOR BLOCKING WHERE BLOCKING IS REQUIRED. WHERE BLOCKING CONTACTS METAL FRAME, STUDS, ETC. SEPARATE WITH BUILDING FELT TO AVOID REACTIONS BETWEEN WOOD AND METALS.
4. ALL WORK AND MATERIALS SHALL COMPLY WITH ALL CITY/COUNTY REGULATIONS AND CODES AND O.S.H.A. STANDARDS.
5. THE SITE WORK FOR THIS PROJECT SHALL MEET OR EXCEED THE "PROJECT SPECIFICATIONS".
6. CONTRACTOR SHALL REFER TO THE ARCHITECTURAL PLANS FOR EXACT LOCATIONS AND DIMENSIONS OF VESTIBULES, SLOPE PAVING, SIDEWALKS, EXIT PORCHES, PRECISE BUILDING DIMENSIONS, EXACT BUILDING UTILITY ENTRANCE LOCATIONS, ETC.
7. CONTRACTOR SHALL BE RESPONSIBLE FOR ALL RELOCATIONS, (UNLESS OTHERWISE NOTED ON PLANS) INCLUDING BUT NOT LIMITED TO, ALL UTILITIES, STORM DRAINAGE, SIGNS, ETC. AS REQUIRED. ALL WORK SHALL BE IN ACCORDANCE WITH GOVERNING AUTHORITIES REQUIREMENTS AND PROJECT SPECIFICATIONS AND SHALL BE APPROVED BY CHAIR. ALL COSTS SHALL BE INCLUDED IN BASE BID.
8. ALL DISTURBED AREAS ARE TO RECEIVE FOUR (4) INCHES OF TOPSOIL, SEED, MULCH AND WATER UNTIL A HEALTHY STAND OF GRASS IS ESTABLISHED.
9. PATCH AND REPAIR EXISTING PAVING WHERE DISTURBED BY NEW CONSTRUCTION BEYOND SAW-CUT JOINT FOR NEW CONSTRUCTION
10. SITE BOUNDARY, TOPOGRAPHY, UTILITY AND ROAD INFORMATION WAS TAKEN FROM A SURVEY BY JOHNSTON SURVEYING OF ROLAND, ARKANSAS.
11. CONTRACTOR TO VISIT SITE TO BECOME FAMILIAR WITH EXISTING CONDITIONS PRIOR TO BIDDING PROJECT. BRING ANY DISCREPANCIES TO THE ATTENTION OF THE ARCHITECT PRIOR TO BID.
12. COORDINATE ALL ROOF PENETRATIONS FOR LOCATION, SIZE AND REQUIRED MATERIALS. ROOFING CONTRACTOR TO INSTALL OR VERIFY INSTALLATION OF ALL PENETRATIONS AND REQUIRED MATERIALS. ROOFING CONTRACTOR TO PROVIDE ALL FLASHING PENETRATIONS, CURBS, CRACKS, TERMINATIONS, ETC. NOT SPECIFICALLY PROVIDED BY OTHER TRADES AND AS REQUIRED FOR WARRANTED INSTALLATION.
13. ALL ROOFING DETAILS (FLASHING, EDGE METAL, PENETRATIONS, CURBS, ETC.) SHALL BE APPROVED BY THE MANUFACTURER AND INCLUDED IN SYSTEM WARRANTY. PROVIDE ALL MATERIAL AND WORK REQUIRED, SHOWN OR NOT, FOR WARRANTED INSTALLATION.
14. ALL METAL ROOFING (INCLUDING TRIM, GUTTERS, DOWNSPOUTS, ETC.) SHALL BE FROM SAME MANUFACTURER, AND SHALL BE INCLUDED UNDER A SINGLE WEATHER TIGHTNESS WARRANTY.




NORTH

 FLOOR PLAN


5
A0.1 1/4" = 1'-0"

RESTROOM FACILITY




DATE: 2025-03-17
PROJECT NO: 24093
DRAWN BY: AR
REV:


A0.1




6 WALL SECTION
A1.1 3/4" = 1'-0"




7 WALL SECTION
A1.1 3/4" = 1'-0"




3 SOUTH ELEVATION
A1.1 1/4" = 1'-0"



1 EAST ELEVATION
A1.1 1/4" = 1'-0"



4 NORTH ELEVATION
A1.1 1/4" = 1'-0"



5 WEST ELEVATION
A1.1 1/4" = 1'-0"

FOUNDATION NOTES:

1. GENERAL CONTRACTOR SHALL VERIFY ALL EXISTING CONDITIONS PRIOR TO COMMENCING WORK. REPORT DISCREPANCIES BETWEEN DRAWINGS AND SITE CONDITIONS TO ARCHITECT FOR COORDINATION.
2. ALL EXISTING UNDERGROUND UTILITIES, FOUNDATIONS, ETC. SHALL BE REMOVED FROM THE AREA OF THE BUILDING PAD AS DIRECTED BY THE GEOTECHNICAL ENGINEER. BACKFILL EXCAVATIONS WITH COMPACTED SELECT FILL AND PLACE PER NOTE 5 BELOW.
3. POSITIVE DRAINAGE AWAY FROM BUILDING PADS SHALL BE PROVIDED AT ALL TIMES. SATURATION OF SUBSURFACE SOILS WILL BE DETRIMENTAL AND MAY INCREASE UNDERCUTS.
4. AT LOCATIONS WHERE UTILITY, ELECTRICAL, OR PLUMBING TRENCHES ARE LOCATED BELOW THE FOOTING AND WITHIN 5 FEET OF THE EDGE OF THE FOOTING, OR BELOW THE FOOTING, TRENCHES SHALL BE BACKFILLED IN LIFTS, COMPACTED, AND TESTED PER NOTE 5
5. ALL COMPACTED FILL SHALL BE PLACED IN 6-INCH LOOSE LIFTS AND COMPACTED TO AT LEAST 95% OF THE MAXIMUM MODIFIED PROCTOR (ASTM D-1557). FILL SOILS SHALL CONSIST OF LOW-PLASTICITY, NON-EXPANSIVE SOILS HAVING A LIQUID LIMIT LESS THAN 40 AND A PLASTICITY INDEX LESS THAN 15. FILL SOILS SHALL BE SELECT CLAYEY SAND (SC), SANDY CLAY (CL), OR CLAY GRAVEL (GC), AS NOTED IN THE SOILS REPORT. THE GEOTECHNICAL ENGINEER SHALL APPROVE ALL MATERIAL TO BE USED FOR FILL OR BACKFILL MATERIAL. PRIOR TO PLACING EACH LIFT, THE PREVIOUS LIFT SHALL BE TESTED AND APPROVED BY GEOTECHNICAL ENGINEER.
6. FLOOR SLABS SHALL BEAR ON A MINIMUM 4" OF WASHED GRAVEL. VAPOR BARRIER (SEE SPECIFICATION 07 26 16) SHALL BE PLACED DIRECTLY BENEATH THE SLAB ON GRADE. BELOW THE WASHED GRAVEL SHALL BE EITHER COMPACTED SELECT FILL OR APPROVED NATURAL MATERIAL PASSING PROOFROLL.
7. FOOTINGS SHALL BEAR ON APPROVED NATURAL UNDISTURBED MATERIAL OR COMPACTED SELECT FILL CAPABLE OF 1,500 PSF ALLOWABLE BEARING CAPACITY. IF SUITABLE BEARING STRATA IS NOT REACHED AT THE BOTTOM OF FOOTING ELEVATION, THE FOOTINGS SHALL BE UNDERCUT UNTIL ACCEPTABLE MATERIAL IS REACHED. FILL UNDERCUT WITH LEAN CONCRETE (300 PSI @ 28 DAYS) TO BOTTOM OF FOOTING ELEVATION. EXCAVATIONS SHALL BE APPROVED BY THE GEOTECHNICAL ENGINEER PRIOR TO PLACING REBAR OR FLOWABLE FILL.
8. SUBGRADE MATERIALS SHALL NOT BE ALLOWED TO DRY OUT DURING EARTHWORK OR FOOTING EXCAVATIONS, NOR SHALL THEY BE ALLOWED TO BECOME SATURATED. FOLLOW GEOTECHNICAL RECOMMENDATIONS REGARDING SITE PREPARATION. IF DURING EARTHWORK OPERATIONS EXPANSIVE SOILS ARE ENCOUNTERED, CONTACT GEOTECHNICAL ENGINEER FOR FURTHER DIRECTION. NOTIFY ARCHITECT PRIOR TO IMPLEMENTING ADDITIONAL UNDERCUT/EARTHWORK.
9. PRIOR TO THE BEGINNING OF THE SITE WORK, THE GENERAL CONTRACTOR SHALL EMPLOY GEOTECHNICAL SERVICES TO OBSERVE SITE WORK OPERATIONS AND PROVIDE RECOMMENDATIONS AS NEEDED TO PROVIDE BEARING STRATUM PER NOTE 7. ANY UNDERCUTS SHALL BE APPROVED BY THE ARCHITECT PRIOR TO UNDERCUTTING.

GENERAL CONCRETE NOTES:

1. AMERICAN CONCRETE INSTITUTE SPECIFICATIONS SHALL GOVERN ALL PHASES OF CONCRETE CONSTRUCTION.
2. CONCRETE PLACEMENT SHALL BE AS NOTED IN THE CONCRETE PLACEMENT SCHEDULE BELOW. SEE SPECIFICATIONS FOR MIX DESIGN REQUIREMENTS.
3. ALL REINFORCING STEEL SHALL BE GRADE 60.
4. GENERAL CONTRACTOR SHALL VERIFY ALL CONCRETE DIMENSIONS, INSERTS, SLEEVES, AND OPENINGS WITH ALL TRADES BEFORE PLACING CONCRETE. ALL SLEEVES FOR CONDUIT, OR OTHER INSERTS SHALL BE PLACED PRIOR TO CONCRETE. NO CONCRETE SHALL BE BROKEN OUT TO PLACE ELECTRICAL, MECHANICAL, OR SIMILAR ITEMS WITHOUT THE PERMISSION OF THE ARCHITECT.
5. VERIFY ALL EXISTING CONDITIONS AND DIMENSIONS PRIOR TO PLACING ANY CONCRETE. IF THERE ARE DISCREPANCIES BETWEEN THE PLANS AND EXISTING CONDITIONS, CONTACT THE ARCHITECT BEFORE COMMENCING WITH WORK.
6. CONCRETE PLACEMENT FOR SLABS SHALL BE CLOSELY COORDINATED WITH WEATHER CONDITIONS TO PREVENT RAPID MOISTURE LOSS OR TEMPERATURE SWINGS. ADEQUATE WIND BREAKS AND COLD/HOT WEATHER PROTECTION SHALL BE PROVIDED TO MAINTAIN ACCEPTABLE TEMPERATURES AT ALL TIMES DURING CURING.
7. 2 WEEKS PRIOR TO PLACING ANY EXPOSED CONCRETE SLABS, THE CONCRETE FINISHER, THE CONCRETE SUPPLIER, ARCHITECT'S REPRESENTATIVE, AND CONTRACTOR SHALL MEET TO DISCUSS MIX DESIGN, ADEQUATE PROTECTION, CURING, SIZE OF SLAB PLACEMENTS, ETC.
8. EXPOSED WALLS AND SLABS SHALL BE REVIEWED FOR CRACKING DETRIMENTAL TO FINISH. SLABS/WALLS TO BE EXPOSED TO VIEW MAY REQUIRE REMOVAL IF THEY ARE DAMAGED OR CRACKING OCCURS THAT WILL BE DETRIMENTAL TO THE FINISH/APPEARANCE OF THE FINAL PRODUCT.

CONCRETE PLACEMENT SCHEDULE	
CONCRETE MIX TYPE	PLACEMENT
4,000 PSI WITH AIR-ENTRAINMENT	EXTERIOR PAVING, CURBS, SIDEWALKS, PADS,
3,000 PSI NO AIR-ENTRAINMENT	INTERIOR FLOOR SLABS, FOOTINGS

WOOD FRAMING NOTES:

1. BRACE AND GUY UNTIL ALL FINAL CONNECTIONS ARE MADE.
2. TIMBER CONSTRUCTION MANUAL BY THE AMERICAN INSTITUTE OF TIMBER CONSTRUCTION SHALL GOVERN ALL PHASES OF DESIGN AND CONSTRUCTION.
3. MATERIALS:
 - WOOD MEMBERS IN CONTACT WITH CONCRETE SHALL BE PRESSURE TREATED.
 - PLYWOOD FOR ROOF DECKING - APA RATED SHEATHING EXPOSURE 1, SEE 8/S2.1 DRAWINGS FOR NAILING AND BLOCKING REQUIREMENTS
 - DIMENSIONAL SAWN LUMBER:
 - A. HEADERS, TOP PLATES, RAFTERS:
 - NO. 2 SOUTHERN PINE OR BETTER
4. REFER TO THE INTERNATIONAL BUILDING CODE 2021 (TABLE 2304.9.1) FOR MINIMUM REQUIREMENTS FOR NAILS AND NAILING FOR ALL CONNECTIONS, UNLESS DETAILED ON THE DRAWINGS OTHERWISE.

BLOCK REINFORCING NOTES:

GENERAL NOTES:

1. MASONRY SHALL MEET THE REQUIREMENTS OF THE SPECIFICATION FOR MASONRY STRUCTURES - TMS 402/606-16.
2. ALL MASONRY SHALL BE INSPECTED AS PER THE LEVEL 2 QUALITY OF ASSURANCE
3. GROUTING OF VERTICAL CELLS SHALL MEET THE REQUIREMENTS OF THE SPECIFICATION FOR MASONRY STRUCTURES AS SET FORTH IN TMS 402/606-16.
4. COMPRESSIVE STRENGTH FOR MASONRY (F_m) SHALL BE 2,000 PSI. ALL MASONRY SHALL BE RUNNING BOND WITH TYPE 'N' MORTAR.
5. VERTICAL REINFORCING MAY BE SPLICED IF REQUIRED. MINIMUM LAP SPLICES SHALL BE AS FOLLOWS:
 - #4 VERTS - 16"
6. ALL VERTICAL CELLS WITH REINFORCING AND BOND BEAMS SHALL BE FILLED WITH MASONRY GROUT WITH A COMPRESSIVE STRENGTH OF 3,000 PSI AT 28 DAYS.
7. SEE DETAIL 1/S2.1 FOR TYPICAL OPENING IN MASONRY WALL.
8. SEE ARCH. DWGS FOR CONTROL JOINTS IN MASONRY WALLS.

VERTICAL REINFORCING:

1. ALL BLOCK WALLS SHALL HAVE ONE FULL HEIGHT REBAR, SIZED AND LOCATED 2/S2.1
2. IN ADDITION, ALL BLOCK WALLS SHALL HAVE ONE VERTICAL BAR (SIZE AS INDICATED ABOVE) AT THE FOLLOWING LOCATIONS:
 - A. AT ENDS OF WALLS.
 - B. AT CORNERS OF WALLS.
 - C. AT WALL INTERSECTIONS.
 - D. AT EACH SIDE OF ALL WALL CONTROL JOINTS.
 - E. AT EACH SIDE OF ALL OPENINGS GREATER THAN 16" WIDE.

HORIZONTAL REINFORCING:

1. ALL 8" BLOCK WALLS SHALL HAVE AN 8" DEEP x 8" WIDE NOMINAL BOND BEAM AT THE TOP OF THE WALL. REINFORCE BOND BEAM WITH (2) #4 REBAR (UNO)
2. HORIZONTAL JOINT REINFORCING SHALL BE CONTINUOUS AND SPACED AT 16" ON CENTER VERTICALLY. MINIMUM LAP IS 12".

BUILDING DESIGN LOADS:

THE FOLLOWING LOADS AS PER IBC 2021 AND THE LATEST EDITION OF THE ARKANSAS FIRE PREVENTION CODE

1. GRAVITY LOADS:
 - a. RAFTERS:
 - UNIFORM DEAD:
 - TOP CHORD = 15 PSF
 - UNIFORM LIVE:
 - TOP CHORD = 20 PSF
2. WIND LOADS:
 - ULTIMATE WIND SPEED (V) = 105 MPH
 - WIND IMPORTANCE FACTOR (I) = 1.0
 - RISK CATEGORY = II
 - INTERNAL PRESSURE COEFFICIENTS (GCp) = ± 1.8
 - EXPOSURE CATEGORY = C
3. SNOW LOAD CRITERIA:
 - GROUND SNOW LOAD (PG) = 10 PSF
 - SNOW EXPOSURE FACTOR (CE) = 1.0
 - IMPORTANCE FACTOR (I) = 1.0
 - THERMAL FACTOR (CT) = 1.0
4. SEISMIC LOAD CRITERIA:
 - RISK CATEGORY = II
 - IMPORTANCE FACTOR = 1.0
 - SPECTRAL RESPONSE COEFFICIENTS
 - I. Ss = 0.15
 - II. S1 = 0.099
 - III. SDs = 0.165
 - IV. SD1 = 0.099
 - SITE CLASS = C (PER SOILS ENGINEER)
 - SEISMIC DESIGN CATEGORY = B
 - BASIC SEISMIC RESISTING SYSTEM
 - ORDINARY REINFORCED MASONRY SHEAR WALLS, R=2
5. CONSTRUCTION LOADS (SCISSORS LIFTS, FORKLIFTS, ETC.) SUPPORTED BY SLABS-ON-GRADE AND STRUCTURAL SLABS SHALL BE ANALYZED BY AN INDEPENDENT STRUCTURAL ENGINEER. THE COST OF THE ANALYSIS SHALL BE PAID FOR BY THE CONTRACTOR. THE ANALYSIS SHALL BE SUBMITTED TO THE ENGINEER OF RECORD FOR APPROVAL. HOWEVER, ENGINEER OF RECORD IS NOT RESPONSIBLE SHOULD DAMAGE TO THE SLAB OR STRUCTURE OCCUR.

SEISMIC NOTE:

I HEREBY CERTIFY THAT THE FRAMING PLANS, FOUNDATION PLANS, STRUCTURAL DETAILS, AND SPECIFICATIONS FOR THIS BUILDING HAVE BEEN PREPARED BY ME OR UNDER MY SUPERVISION. I FURTHER CERTIFY THAT TO THE BEST OF MY KNOWLEDGE THE PLANS AND SPECIFICATIONS ARE AS REQUIRED AND IN COMPLIANCE WITH ACT 1100 (SEISMIC LAW). REFER TO THE BUILDING DESIGN LOADS ON THIS SHEET FOR SEISMIC DESIGN CRITERIA.

DATE: FEBRUARY 14, 2025



RANDY L. GANGLUFF, P.E., AR #11242

STRUCTURAL LEGEND:

BRG.	BEARING
CLR.	CLEAR
EF	EACH FACE
EJ	EXPANSION JOINT
EQ	EQUAL
EW	EACH WAY
FD	FLOOR DRAIN (24"Ø WALLOW, SLOPE SLAB 1/2" TO DRAIN)
FF	FINISHED FLOOR
FG	FINISHED GRADE
H	HIGH
LG	LONG
O.C.	ON CENTER
O.H.	OPPOSITE HAND
SCJ	SAWN CONTROL JOINT - SEE 4/S2.1
SIM.	SIMILAR
TOW	TOP OF WALL
UNO	UNLESS NOTED OTHERWISE
VIF	VERIFY IN FIELD
WWF	WELDED WIRE FABRIC
---	DENOTES SAWN CONTROL JOINT

SPECIAL INSPECTIONS:


SPECIAL INSPECTIONS ARE NOT REQUIRED FOR STRUCTURAL SYSTEM.



225009


RESTROOM FACILITY

SAU TECH
CAMDEN, ARKANSAS




DATE: 2025 03-17
PROJECT NO: 24093
DRAWN BY: GGGAE
REV:


S1.1





1 TYPICAL MASONRY OPENING
S2.1 NTS




2 EXTERIOR WALL FOOTING
S2.1 3/4"=1'-0"




3 TYPICAL EXTERIOR DOOR FOOTING
S2.1 3/4"=1'-0"





4 TYPICAL INTERIOR BLOCK WALL (UNO)
S2.1 3/4"=1'-0"




5 WOOD RAFTERS BEARING ON MASONRY WALL
S2.1 3/4"=1'-0"




6 ROOF FRAMING @ END WALL
S2.1 3/4"=1'-0"



7 WOOD RAFTERS BEARING ON MASONRY WALL
S2.1 3/4"=1'-0"



8 TYP. ROOF SHEATHING DIAGRAM
S2.1 3/4"=1'-0"



9 TYPICAL LINTEL
S2.1 3/4"=1'-0"

PLAN NOTES:

- SEE S1.1 FOR THE FOLLOWING:
 - FOUNDATION NOTES
 - CONCRETE NOTES
 - BLOCK REINFORCING NOTES
 - WOOD FRAMING NOTES
 - BUILDING DESIGN LOADS
 - LEGEND
- DIMENSIONS SHOWN ARE TO OUTSIDE FACE OF BLOCK. SEE ARCH FOR ADD'L LAYOUT DIMENSIONS.
- VERIFY ALL DIMENSIONS WITH ARCHITECT'S DRAWINGS AND SITE CONDITIONS PRIOR TO CONSTRUCTION.



PLUMBING FIXTURE SCHEDULE

PLUMBING SPECIFICATIONS



MECHANICAL GENERAL NOTES	
1.	DUE TO THE SMALL SCALE OF THIS DRAWING, IT IS NOT POSSIBLE TO INDICATE ALL OFFSETS, FITTINGS AND ACCESSORIES WHICH MAY BE REQUIRED. THE CONTRACTOR SHALL INVESTIGATE THE STRUCTURAL AND FINISH CONDITIONS AFFECTING THE WORK AND SHALL COORDINATE AND ARRANGE HIS WORK ACCORDINGLY.
2.	EXHAUST DUCTWORK SHALL BE UNINSULATED, UNLESS OTHERWISE NOTED.
3.	COORDINATE LOCATION OF DUCTS AND FANS WITH STRUCTURAL FRAMING MEMBER. OFFSET DUCTS AS REQUIRED TO CLEAR STRUCTURAL MEMBERS.
4.	COORDINATE LOCATIONS AND ELEVATION OF DUCT RUNS WITH PLUMBING AND ELECTRICAL CONTRACTORS.
5.	COORDINATE EQUIPMENT ELECTRICAL REQUIREMENTS WITH ELECTRICAL CONTRACTOR.
6.	SCREWS TO SECURE AIR DEVICES SHALL BE PAINTED HEAD TYPE PROVIDED BY DEVICE MANUFACTURER. ANY OTHER TYPE USED WILL BE REPLACED WITH PROPER SCREW BEFORE ACCEPTANCE.

HVAC ABBREVIATIONS	
(SEE SHT T-1 FOR GENERAL ABBREVIATIONS)	
A.F.F.	ABOVE FINISHED FLOOR
ABV.	ABOVE
CFM	CUBIC FEET PER MINUTE
DISCH.	DISCHARGE
DN.	DOWN
MIN.	MINIMUM
OSA	OUTSIDE AIR
PLUMB.	PLUMBING
R.A.	RETURN AIR
S.A.	SUPPLY AIR
T-STAT	THERMOSTAT
U.N.O.	UNLESS NOTED OTHERWISE
W/	WITH
I.D.	INTERNAL DIAMETER
EXT. INSUL.	EXTERNALLY INSULATED

MECHANICAL LEGEND	
	DETAIL NUMBER
	TOP NUMBER INDICATES DETAIL NUMBER BOTTOM NUMBER INDICATES SHEET NUMBER



HVAC SEISMIC NOTES	
1.	SAU TECH EMS BUILDING IS CLASSIFIED AS SEISMIC DESIGN CATEGORY B AND RISK CATEGORY II WITH A COMPONENT IMPORTANCE FACTOR OF (Ip) = 1.0.
2.	THE CONTRACTOR SHALL BE FAMILIAR WITH THE 2021 INTERNATIONAL BUILDING CODE (IBC) AND ARKANSAS AMENDMENTS SUCH THAT THE SYSTEMS AND THE COMPONENTS ARE INSTALLED TO COMPLY.
3.	BECAUSE THE COMPONENTS OF THESE FACILITIES HAVE A COMPONENT IMPORTANCE FACTOR (Ip) = 1.0, THE MECHANICAL COMPONENTS ARE EXEMPT FROM THE REQUIREMENTS OF THE SECTION.

EXHAUST FANS SCHEDULE											
MARK	MANUFACTURER	MODEL	TYPE	CFM	E.S.P. (IN W.G.)	VOLTAGE / PHASE	FAN HP (HP OR WATTS)	SONES	WEIGHT (LBS)	CONTROL POINT	NOTES
EF-1	GREENHECK	SP-B110	CEILING	75	0.3	120/1	80.0	0.6	13	SWITCH	1, 2, 3
EF-2	GREENHECK	SP-B110	CEILING	75	0.3	120/1	80.0	0.6	13	SWITCH	1, 2, 3

- ACCESSORIES & NOTES:
- PROVIDE HANGING RODS AND VIBRATION ISOLATORS AS REQUIRED.
 - PROVIDE FACTORY MOUNTED SOLID STATE SPEED CONTROLLER AT FAN, INTERNAL DISCONNECT AND BACKDRAFT DAMPER.
 - PROVIDE W/ WHITE ALUMINUM CEILING GRILLE.
 - MOUNT FAN LEVEL AT SLOPED CEILING.


ELECTRIC HEATER SCHEDULE							
MARK	MANUFACTURER	MODEL	HEATING (KW)	BTU'S	VOLTAGE / PHASE	AMPS	WEIGHT (LBS)
EH-1	MARKEL	H3423T	3	10,239	240/1	14.4	41
EH-2	MARKEL	H3423T	3	10,239	240/1	14.4	41

- ACCESSORIES & NOTES:
- PROVIDE W/ INTEGRAL T-STAT / DISCONNECT.
 - PROVIDE SEMI RECESSED WALL BOX
 - MOUNT AT 12" AFF TO BOTTOM



LIGHT FIXTURE SCHEDULE						
MARK	DESCRIPTION	MANUFACTURER	MODEL	WATTAGE	VOLTAGE	NOTES
D	LINEAR UTILITY STRIP FIXTURE	Columbia	MPS4-10-VW-FW-EDU	26.5	UNV	CHAIN MOUNT TO +10'-0" AFF WHERE NO CEILING
G	WALL MOUNT EXTERIOR EGRESS FIXTURE	DualLite	PG-FINISH-HTR	15.2	UNV	WALL MOUNT AT +8'-0" AFF - UNO
R	WALL MOUNT TWO-HEADED EMERGENCY EGRESS LIGHT	DualLite	EVHC-6-FINISH	6	UNV	WALL MOUNT AT +9'-0" AFF - UNO
W	EXTERIOR WALL MOUNT ARCHITECTURAL AREA LIGHT	Current	PRS-20-4K-PC	53	UNV	REFER TO ARCH ELEVATIONS FOR MOUNTING HEIGHT(S)


- COMMENTS:
1. ALL HEIGHTS ARE IN REGARDS TO THE CENTERLINE OF FIXTURE - UNO.
 2. ALL EXIT SIGNS SHALL BE PROVIDED WITH THE PROPER FACES/CHEVRONS AS REQUIRED. ALL EXIT SIGNS AND "R"/"G" EGRESS ONLY TYPE FIXTURES ARE TO BE NON-SWITCHED.
 3. CONTRACTOR SHALL PROVIDE/SUBMIT COMPATIBLE LOW-VOLTAGE DIMMER SWITCHES WITH THE FINAL SELECTED FIXTURE SUBMITTALS.



1
E1.1

FLOOR PLAN - TLT - LIGHTING

1/4" = 1'-0"



3
E1.1

FLOOR PLAN - TLT - POWER

1/4" = 1'-0"


ELECTRICAL GENERAL NOTES

1. DUE TO THE SMALL SCALE OF THE PLANS AND THE DIAGRAMATIC NATURE OF ELECTRICAL PLANS IN GENERAL IT IS NOT POSSIBLE TO INDICATE ALL OFFSETS, FITTINGS, JUNCTION BOXES, ETC. WHICH MAY BE REQUIRED. THE CONTRACTOR SHALL INVESTIGATE THE STRUCTURAL AND FINISH CONDITIONS AFFECTING HIS WORK AND SHALL COORDINATE AND ARRANGE HIS WORK ACCORDINGLY.
2. PROVIDE LAMINATED NAMEPLATES ON ALL ELECTRICAL GEAR PER THE SPECIFICATIONS. SCREW OR POP RIVET TO COVERS. ALL SAFETY SWITCHES SHALL BE HEAVY DUTY, NON-FUSED, 240V OR 600V, SOLID NEUTRAL, NEMA 1 OR NEMA 3R AS APPLIES UNLESS NOTED OTHERWISE.
3. MINIMUM CONDUIT SIZE SHALL BE 3/4" UNLESS NOTED OTHERWISE. SLEEVE ALL RACEWAYS ROUTED THRU FOOTINGS OR GRADE BEAMS. CONTRACTOR SHALL FIRESTOP PER SPECIFICATIONS ALL CONDUIT PENETRATIONS THRU RATED WALLS. VERIFY FIRE RATED WALL LOCATIONS WITH ARCHITECTURAL PLANS. CONTRACTOR SHALL COORDINATE WITH PLUMBING CONTRACTOR AND AVOID ANY WATER CARRYING PIPE INSTALLATION ABOVE ELECTRICAL GEAR AND/OR APPARATUS. SET SCREW AND IDENTER TYPE CONDUIT FITTINGS ARE NOT ALLOWED. ALL INTERIOR EXPOSED RACEWAY SHALL BE PAINTED AS DIRECTED BY ARCHITECT.
4. ALL CONDUIT, JUNCTION AND OUTLET BOXES, AND RELATED ROUGH-IN MATERIAL ARE TO BE CONCEALED UNDER FLOORS, IN WALLS AND ABOVE FINISHED CEILINGS WHERE POSSIBLE UNLESS NOTED OTHERWISE IN THE SPECIFICATIONS OR ON THE DRAWINGS. ALL CONDUITS SHALL BE ROUTED OVERHEAD UNLESS NOTED OTHERWISE OR SHOWN AS BELOW GRADE TO A DEVICE.
5. ALL CONDUCTORS SHALL BE COPPER WITH A MINIMUM SIZE CONDUCTOR OF #12 A.W.G. PROVIDE SOLID TYPE "THW" OR "THHN" FOR #12 A.W.G. AND #10 A.W.G. ALL FEEDER AND MOTOR/EQUIPMENT CONDUCTORS SHALL BE COPPER TYPE "THW" OR "THWN".
6. ALL EQUIPMENT SHALL BE BRACED FOR EARTHQUAKE. LIGHT FIXTURES TO HAVE EARTHQUAKE CLIPS AND INDEPENDENT SUPPORT WIRES AT OPPOSITE CORNERS. ALL CEILING MOUNTED EQUIPMENT SUCH AS LIGHT FIXTURES SHALL BE SECURED TO THE STRUCTURE WITH #12 GA STEEL WIRE ON TWO (2) SIDES. IN ADDITION, LIGHT FIXTURES SHALL BE SECURED TO THE CEILING WITH FACTORY UL LISTED EARTHQUAKE CLIPS.
7. AT LOCATIONS WHERE TRENCHES ARE BELOW BOTTOM OF FOOTING ELEVATION AND WITHIN SIX FEET OF THE EDGE OF THE FOOTING, TRENCHES SHALL BE BACKFILLED IN LIFTS, COMPACTED AND TESTED. REFER TO STRUCTURAL DRAWINGS FOR FOUNDATION NOTES FOR BACKFILL PROCEDURES. PROVIDE PULLSTRINGS FOR ALL CONDUIT STUBS/SLEEVES.
8. PROVIDE A MIN. OF (2) 4" ON BOTH SIDES OF CORRIDOR PARTITIONS. PROVIDE (2) 3M #17RD FIRE-RATED SEALS AT FIRE-RATED PARTITIONS. PROVIDE SPEC-SEAL FIRESTOP PILLOWS IN ALL OTHER SLEEVES AND PENETRATIONS AT FIRE-RATED WALLS.
9. ALL CIRCUITS, LIGHTING AND POWER, SHALL HAVE DEDICATED NEUTRAL CONDUCTORS WITH ONE PER EACH HOT CONDUCTOR-(NO SHARING OF NEUTRALS). ONLY 3 "HOT" CIRCUITS ALLOWED PER HOMERUN - U.N.O.
10. ALL OF THE FOLLOWING RECEPTACLES SHALL BE GFCI TYPE:
a.) RECEPTACLES FOR ELECTRIC WATER COOLERS
b.) RECEPTACLES IN BATHROOMS OR WITHIN 5'-0" OF A SINK
c.) NEMA 5-20R RECEPTACLES FOR A KITCHEN OR CONCESSION AREA.
d.) EXTERIOR RECEPTACLES SHALL BE GFCI AND WEATHER RESISTANT "WR" TYPE.
Note: FEED THROUGH PROTECTION OF GFCI OUTLETS ARE NOT ALLOWED.
11. MOUNT EXTERIOR DISCONNECTS FOR HVAC/MECHANICAL EQUIPMENT AT +48" A.F.G. TO TOP OF DISCONNECT OR, WHERE APPLICABLE, TOP OF DISCONNECT AT TOP OF ADJACENT SURROUNDING SCREEN WALL, WHICHEVER IS LOWER. COORDINATE LOCATIONS OF ALL DISCONNECTS WITH FINAL EQUIPMENT LOCATIONS PRIOR TO BEGINNING WORK AS NOT TO IMPEDE ANY EQUIPMENT ACCESS OR VIOLATE ANY NEC CLEARANCES REQUIREMENTS.
12. THE FINAL TYPEWRITTEN ELECTRICAL PANEL SCHEDULES SHALL REFLECT THE ACTUAL ROOM DESCRIPTIONS AND NUMBERS DEPICTED ON FINAL INSTALLED ROOM SIGNAGE. (FIELD VERIFY FOR ACCURACY).
13. LOW-VOLTAGE, AUDIO/VISUAL, AND INTERACTIVE DISPLAY BOARD CONDUITS ARE SIZED IN ACCORDANCE WITH VENDORS INSTALLING/UTILIZING "RAPIDRUN" OR "EZ-PULL" TYPE CABLES TO EQUIPMENT. CONTRACTORS PROVIDING AUDIO/VISUAL CABLING UNDER THIS PROJECT/CONTRACT SHALL UTILIZE THESE TYPES OF CABLES.
14. LIGHT FIXTURES SUBMITTED/PROVIDED SHALL MEET THE REQUIREMENTS OF THE DESIGNLIGHTS CONSORTIUM AND/OR BE ENERGYSTAR CERTIFIED.
15. CONTRACTOR IS RESPONSIBLE FOR PROVIDING AND SUBMITTING ALL POWER PACKS, RELAYS, SENSORS, CABLING, ETC AS REQUIRED TO PROVIDE COMPLETE AND OPERATIONAL OCCUPANCY CONTROLS IN COMPLIANCE WITH THE LATEST ENERGY CODES.
16. ALL CONDUITS ENTERING THE BUILDING FROM BELOW GRADE SHALL BE SEALED OFF FROM WATER INFILTRATION WITH CONDUIT SEALANT SYSTEM EQUAL TO POLY-WATER FST SYSTEM. ALL EMPTY STUBBED UP CONDUITS SHALL ALSO BE PROVIDE WITH THREADED CAP FOR COVER.
17. PROVIDE HANDLE-LOCK-OFF TYPE BREAKERS FOR ALL CIRCUITS FEEDING ELECTRIC RESISTIVE HEATERS (EH#1, CH#4, EDH# FOR EXAMPLE).
18. PROVIDE TAMPER-RESISTANT TYPE RECEPTACLES IN ALL LOCATIONS AS REQUIRED BY NEC 406.12

NAMEPLATE NOTES

1. ALL ELECTRICAL EQUIPMENT, TIMER SWITCHES, SAFETY SWITCHES, STARTERS, PANELS, AND TRANSFORMERS SHALL HAVE LAMINATED BAKELITE NAMEPLATES SECURELY FASTENED TO DEVICE.
2. NAMEPLATE SIZE SHALL BE 1 1/2" x 4" WITH BEVELED EDGES AND 1/4" LETTERS.
3. NAMEPLATE SHALL INCLUDE PANEL OR EQUIPMENT DESIGNATION, INCLUDE AMPERAGE, VOLTAGE, PHASE, AND WIRE FOR THE PANELS, AND "PANEL FED FROM" FOR THE EQUIPMENT.
4. NAMEPLATES SHALL BE INSTALLED TO PANELS, CABINETS, SWITCHES, ETC. WITH RIVETS OR STAINLESS STEEL SCREWS. PLATES ATTACHED TO DRYWALL OR BLOCK ON INTERIOR MAY BE ADHESIVE BACK.
5. NAMEPLATES FOR 120 OR 208 VOLT EQUIPMENT SHALL BE BLACK, 277 OR 480 VOLT EQUIPMENT SHALL BE RED. LETTERS SHALL BE WHITE.
6. EMBOSSED STICK BACK WILL NOT BE ALLOWED.
7. NAMEPLATES FOR SWITCHES MAY BE OMITTED FOR FURNACES WHEN THE EQUIPMENT WHICH IS SERVED IS OBVIOUS TO SERVICE TECHNICIAN.
8. WHERE EQUIPMENT DISCONNECT IS AT A PANEL, SECURE NAMEPLATE (WITH UNIT DESIGNATION AND "FED FROM PANEL") TO THE EQUIPMENT.

EQUIP TAG DETAIL




OCC SENSOR DETAIL

5 E2.1 NOT TO SCALE

MINIMUM WIRING NOTES


WHETHER SHOWN OR NOT - THE CONTRACTOR SHALL PROVIDE THE MINIMUM WIRE NOTED BELOW FOR ALL EQUIPMENT CONNECTIONS:

MCCB/BREAKER	WIRE:
20A	#12AWG
25A-30A	#10AWG
35A-40A	#8AWG
45A-55A	#6AWG
55A-70A	#4AWG
70A-85A	#3AWG
85A-100A	#2AWG




OCC SENSOR MOUNT GENERAL

6 E2.1 NOT TO SCALE



RECEPTACLE GROUND DETAIL

8 E2.1 NOT TO SCALE



TWH CONNECTION

4 E2.1 NOT TO SCALE

ELECTRICAL SYMBOL LEGEND


SYMBOL	DESCRIPTION
[Symbol]	INTERIOR FIRE ALARM HORN/SPKR - MTD. AT 80\"/>
[Symbol]	FIRE ALARM, STROBE ONLY, 80\"/>
[Symbol]	FIRE ALARM, SPKR / STROBE COMBINATION, 80\"/>
[Symbol]	FIRE ALARM STATION - PULL STATION, 4\"/>
[Symbol]	WATER SUPERVISORY TAMPER SWITCH
[Symbol]	MAGNETIC DOOR HOLD OPEN - TYPE AS NOTED IN FIRE ALARM GENERAL NOTES/SPECIFICATIONS.
[Symbol]	SD - SMOKE DETECTOR - AUTOMATIC, ADDRESSABLE, CEILING MOUNTED
[Symbol]	HD - HEAT DETECTOR - AUTOMATIC, ADDRESSABLE, CEILING MOUNTED
[Symbol]	'DS'D DENOTES DUCT SMOKE DETECTOR (SUPPLY/RET-RETURN)
[Symbol]	FIRE ALARM, STROBE ONLY, CEILING MOUNT
[Symbol]	FA NOTES: *OF - CANDLE RATING
[Symbol]	FA CEILING SPKR / STROBE COMBINATION
[Symbol]	FA CEILING SPEAKER ONLY
[Symbol]	WATER SUPERVISORY FLOW SWITCH
[Symbol]	REMOTE TEST/STATUS STATION
[Symbol]	INDICATES FA ADDRESSABLE RELAY
HEIGHT:	[+48\", IN REGARDS TO FIRE ALARM, IS TO THE TOP OF BOX] [+80\", IN REGARDS TO FIRE ALARM, IS TO THE BOTTOM OF BOX]
[Symbol]	CATV COAX OUTLET - MOUNT AT HEIGHT NOTED (F-CONNECTOR)
[Symbol]	VOICE/TELEPHONE JACK OUTLET @ 18\"/>
[Symbol]	DATA/COMPUTER JACK OUTLET @ 18\"/>
[Symbol]	COMPUTER/TELE. COMBO OUTLET @ 18\"/>
[Symbol]	WIRELESS ACCESS POINT - CEILING
[Symbol]	FLUSH MOUNTED FLOOR BOX, SEE PLANS FOR COORD WITH POWER FLOOR BOX(ES) TELE/DATA OR COMBO AS INDICATED (MULTI-GANG WALKER RF86-OG - U.N.O.)
[Symbol]	COMBINATION RECEPTACLE AND LOW-VOLTAGE 'AV' CABLING IN MULTI-GANG BOX MOUNT AT HEIGHT NOTED/DETAILED ON RISER
[Symbol]	TELECOM TERMINAL BOARD, 4FTx8FTx3/4\"/>
[Symbol]	CABLE TRAY - TYPE AND MOUNTING AS DETAILED
HEIGHT:	[IN REGARDS TO TELECOM, MATCH RECEPTACLE HEIGHTS: +18\"/>

SYMBOL	DESCRIPTION
[Symbol]	BELL - MTD. AT 12\"/>
[Symbol]	DOOR BUZZER
[Symbol]	INTERCOM CALL-SWITCH, 4\"/>
[Symbol]	INTERCOM TWO-WAY TELEPHONE HANDSET, MOUNT 4\"/>
[Symbol]	DIGITAL CLOCK-MTD. AT 12\"/>
[Symbol]	SPEAKER - CEILING MOUNTED 8\"/>
[Symbol]	INTERCOM/PAINGING U.N.O. / ('S') INDICATES SINGLE-FACE [RN INDICATES SOUND REINFORCE, FA - FIRE, AV-AUDIO/VISUAL]
[Symbol]	SPEAKER - WALL MOUNTED 12\"/>
[Symbol]	LOUDSPEAKER/HORN - MOUNT AT HEIGHT NOTED (11\"/>
[Symbol]	VOLUME CONTROL
[Symbol]	MICROPHONE OUTLET
HEIGHT:	[+48\", IN REGARDS TO INTERCOM, IS TO THE TOP OF BOX]
[Symbol]	KEYPAD - INTRUS.
[Symbol]	MAGNETIC CONTACT(SECURITY)
[Symbol]	ELECTROMAGNETIC LOCK - ACCESS CONTROL
[Symbol]	PIR SENSOR FOR DOOR RELEASE
[Symbol]	SECURITY/DOOR POWER SUPPLY
[Symbol]	ELECT POWER TRANSFER HINGE
[Symbol]	PANIC HARDWARE DOOR RELEASE
[Symbol]	CARD READER - ACCESS
[Symbol]	EXIT REQUEST BUTTON - ACCESS CONTROL
[Symbol]	READER CONTROLLER
[Symbol]	DOOR RELEASE PB / TWO-WAY INTERCOM
[Symbol]	MOTION DETECTOR / GLASS BREAK
[Symbol]	ELECTRIC DOOR STRIKE /
[Symbol]	ELECTRIC LATCH
[Symbol]	CEILING CAMERA - CCTV
[Symbol]	WALL CAMERA - CCTV
HEIGHT:	[IN REGARDS TO SECURITY, +48\"/>

SYMBOL	DESCRIPTION
[Symbol]	THERMOSTAT/TEMP SENSOR - PROVIDE BOX AS REQ'D BY MECHANICAL AT 4\"/>
[Symbol]	MULTIOUTLET ASSEMBLY (TYPE DENOTED)
[Symbol]	SOLENOID VALVE
[Symbol]	JUNCTION BOX - FINAL CONNECTION TO EQUIPMENT AS REQUIRED
[Symbol]	EQUIPMENT J-BOX - TYPE AS SHOWN/NOTED - CONNECT TO EQUIPMENT AS REQUIRED
[Symbol]	WIRE DESIGNATIONS - HOT, SWITCH, NEUTRAL, GROUND, ISOLATED GROUND, RESPECTIVELY.
[Symbol]	WIRE IN CONDUIT-CEILING OR WALL
[Symbol]	HOMERUN TO PANEL
[Symbol]	CONDUIT STUB/SLEEVE
[Symbol]	WEATHERHEAD - SIZE AS NOTED ON PLANS
[Symbol]	WIRE IN CONDUIT - UNDERFLOOR (SEE REQ'S IN SPECS)
ABBREVIATIONS:	
WP - WEATHERPROOF (3R)	
NS - NON-SWITCHED	
EM - INDICATES EMERGENCY EGRESS FIXTURE	
TC - TIME CLOCK	
LC - LIGHTING CONTACTOR	
FA - FIRE ALARM	
EWC - ELECTRIC WATER COOLER(GFI BREAKER)	
U.N.O. - UNLESS NOTED OTHERWISE	
ER - EXISTING RELOCATED	
WG - WIRE PROTECTIVE GUARD	
1G/1G - SINGLE GANG BOX / SINGLE GANG RING	
-DASHED INDICATES EXISTING OR BELOW GRADE AS NOTED	
AC - ABOVE COUNTER	
HP - HORSEPOWER	
C - CONDUIT ('EMT' OR 'RIGID' AS SPECIFIED)	
PVC - ELECT GRADE PVC CONDUIT (SCH. AS NOTED)	
WM - SURFACE MOUNTED RACEWAY (WIREMOLD)	
AV - INDICATES AUDIO/VISUAL DEVICES	
SB - INDICATES INTERACTIVE DISPLAY BOARD	
A.F.F. - INDICATES ABOVE FINISHED FLOOR	
A.F.G. - INDICATES ABOVE FINISHED GRADE	
B.F.G. - INDICATES BELOW FINISHED GRADE	
F.D.S. - FUSIBLE DISCONNECT SWITCH	
N.F.D.S. - NON-FUSIBLE DISCONNECT SWITCH	
RECEPTACLES	
GFCI INDICATES GROUND FAULT CIRCUIT INTERRUPTER TYPE	
CLG INDICATES CEILING	
T INDICATES TAMPER-RESISTANT TYPE	
U INDICATES DUPLEX POWER WITH 'USB' OUTLETS	
IG INDICATES ISOLATED GROUND TYPE (PROVIDE SEPARATE NEUTRALS/GROUNDS ON ALL 'IG' CIRCUITS)	
---EOHE--- EXISTING OVERHEAD ELECTRICAL	
---EUGE--- EXISTING UNDERGROUND ELECTRICAL	
---OHE--- OVERHEAD ELECTRICAL	
---UGE--- UNDERGROUND ELECTRICAL	
---UGT--- UNDERGROUND TELEPHONE	
---UTV--- UNDERGROUND CABLE (TELEVISION)	
---UFO--- UNDERGROUND FIBER OPTIC	
---UC--- UNDERGROUND SYSTEMS CONDUIT	
---X---X--- INDICATES UTILITY TO BE REMOVED	
(P) - (S)	[P-INDICATES PRIMARY: S-INDICATES SECONDARY]

RESTROOM FACILITY

SAU TECH
CAMDEN, ARKANSAS



DATE: 2025 03-17
PROJECT NO: 24093
DRAWN BY: SWML
REV:

E2.1

ELLIOTT • MCMORRAN • VADEN
RAGSDALE • WOODWARD • INCORPORATED
501 223 9302 • WWW.LEMVRW.COM

LEWIS
ARCHITECTS
ENGINEERS